

NS-396-G

Mechanical/Electrical Grease

A synthetic grease designed for use as a mechanical lubricant as well as an electrical contact interface lubricant. This product is suitable for low current (milliamp) and high current applications requiring low arc-switching debris, durability, and non-ferrous (e.g. Copper, Brass, Silver) corrosion protection over a range of -40°C to +149°C (-40°F to +300°F). NS-396-G exhibits excellent mechanical stability and low fluid migration, with low evaporation at high temperatures. Lower mechanical friction and improved anti-wear at higher temperatures is also exhibited. May be used in switches, small gearboxes, wiper motors, cables and other similar devices.

Characteristics:

- Wide temperature range -40°C to +149°C (-40°F to +300°F)
- Excellent Cu & Ag corrosion protection in humidity & dry situations
- Used on low milliamp and arc-switching sliding contacts
- Very high mechanical stability and low migration
- Extremely low evaporation rate

Typical Properties

Color	Cream
Thickener	Li Soap
Penetration, ASTM D1403, worked, 60 Ds	295
Dropping point, ASTM D2265, °C, min	200
Oil Separation, ASTM D6184-98, 24 hrs. @ 212°F, %	6.5
Specific gravity, 60/60°F	0.83
Evaporation Loss, ASTM D972, 22 hrs., 100°C, %	0.2
Copper corrosion, ASTM D4048, 24 hrs. @ 100°C	1b

Typical Base Fluid Properties

Base fluid	PAO
Viscosity, ASTM D445 @ 40°C, cSt	69
Viscosity, ASTM D445 @ 100°C, cSt	10.6
Viscosity Index Extended, ASTM D2270	141

Material Compatibilities:

Compatible with most engineering plastics including ABS and polycarbonate. Not for use with Buna S, Butyl, EPDM, EPR, or natural rubber elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

03/17 Rev.5

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA
(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems