

NS-40018-GL2

Low Viscosity Damping Lubricant

A silicone fluid based PTFE enhanced grease formulated for applications requiring a lubricant with damping and noise control properties. High stability, low migration and oil separation, multi-plastics compatibility and wide operating temperature range are additional features of this product. Good anti-wear for plastic to plastic or metal to plastic and other lightly loaded mechanical interfaces. Applications might include automotive cabin components such as visor hinges, bearings, plastic gears, push-pull cables and slides.

Characteristics:

- Good noise and squeek control
- High film strength
- Moisture resistant
- Wide temperature range (-65°C to 125°C)
- Non-melting with a low migration rate
- Plastics friendly
- Reduced oil separation

Typical Properties

Color	White
NLGI grade	2
Oil Separation, FTM 321.3, 24 hrs. @ 100°C, %	2
Dropping point, ASTM D2265, °F(°C)	>500(260)
Thickener	Inorganic
Copper corrosion, 24 hrs. @ 100°C	1b

Typical Base Fluid Properties

Viscosity, ASTM D445 @ 25°C, cSt	50
Viscosity, ASTM D445 @ 100°C, cSt	16
Pour point, ASTM D97, °F(°C)	<-94(-70)
Flash point, ASTM D92, °F(°C)	>540(282)

Material Compatibilities:

Compatible with most engineering plastics and elastomers. Not for use with silicone rubber. Check with material manufacturer or Syn-Tech concerning compatibility.

10/07 Rev.0

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA
(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems