

NS-50040-GC

Synthetic Electrical Connector Lubricant

NS-50040-GC is an electrical connector grease for both ferrous and non-ferrous metals. Specifically formulated for long life corrosion protection, vibration damping, fretting control and moisture resistance in elevated temperature environments. Contains a UV tracer.

Characteristics:

- Atmospheric corrosion protection for ferrous and non-ferrous metals
- Reduces connector fretting
- Resistant to water washout
- High mechanical stability
- Low migration
- UV Tracer responds well to 395 nm UV light

Typical Properties

NLGI grade	2
Penetration, ASTM D217, worked, 60 DS	275
Dropping point, ASTM D2265, °F(°C) min.	>500(260)
Oil Separation, FTM 321.3, 24 hrs. @ 212°F, %	1
Copper corrosion, ASTM D130, 3 hrs. @ 210°F	1a
Thickener	Inorganic

Typical Base Fluid Properties

Base fluid	PAO
Viscosity Index, ASTM D2270	150
Viscosity, ASTM D445 @ 40°C, cSt	395
Viscosity, ASTM D445 @ 100°C, cSt	40
Flash point, ASTM D92, °C	295
Pour point, ASTM D97, °C	-30

Material Compatibilities:

Compatible with most engineering plastics including ABS and polycarbonate. Not for use with Buna S, Butyl, EPDM, EPR, or natural rubber elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

12/17 Rev.1

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA
(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems