

# NS-5115-G

## Water Resistant Synthetic Antiwear Grease

---

NS-5115-G is a fully synthetic NLGI 2 grease formulated to provide friction reduction, antiwear and mild EP protection with premium corrosion protection for gears and bearings. A high viscosity index synthetic hydrocarbon (PAO) base fluid provides low drag lubrication for lower operating temperatures over a wide temperature range of -40°C to 200°C (-40°F to 392°F). Its shear resistant calcium sulfonate complex thickener system provides a consistent lubrication film and is extremely resistant to moisture, humidity and steam. NS-5115-G works very well as a seal lubricant in pneumatic cylinders.

### Characteristics:

- Fully synthetic formula
- Calcium sulfonate complex thickener
- Excellent antiwear performance
- Excellent resistance to water washout and sprayoff
- High resistance to breakdown due to steam
- Superior rust and corrosion protection
- Low volatility

### Typical Properties

Color	Tan
Thickener	CaS Complex
NLGI grade	2
Oil Separation, ASTM D6184, 24 hrs. @ 100°C, %, Max	<0.5
Dropping point, ASTM D2265, °C(°F)	>315(599)
4-Ball Wear, ASTM D2266, 60 min, 1200 rpm, mm.	0.45
Copper corrosion, 24 hrs. @ 100°C	1b
Rust Prevention, ASTM 1743	Pass
WaterWashout, % removed, ASTM D1264	<1
Water Sprayoff, ASTM 4049, %	<30

### Typical Base Fluid Properties

Base fluid	PAO
Viscosity, ASTM D445 @ 40°C, cSt	30
Viscosity, ASTM D445 @ 100°C, cSt	5.9
Viscosity Index Extended, ASTM D2270	145
Pour point, ASTM D97, °C(°F)	-65(-85)

### Material Compatibilities:

Compatible with most engineering plastics including ABS and polycarbonate. Not for use with Buna S, Butyl, EPDM, EPR, or natural rubber elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

01/18 Rev.3

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



---

1550F W. Fullerton Ave.  
Addison, IL 60101 USA  
(630) 628-7290  
[www.syn-techlube.com](http://www.syn-techlube.com)

**Lubricants that Solve Problems**