

# NS-1514-G

## Synthetic Calcium Sulfonate Complex Grease

---

NS-1514-G is a food grade synthetic hydrocarbon based grease with a calcium sulfonate complex thickener. This product provides load carrying performance and reduced component wear. This grease also has excellent corrosion protection and superior water washout and spray off properties for bearings and gears.

### Characteristics:

- Antiwear performance
- Food grade
- Resistant to water washout and spray off
- High oxidation resistance
- Excellent rust and corrosion protection
- Excellent mechanical stability
- High drop point
- Operating temperature range of -30°C to 170°C (-22°F to 338°F)

### Typical Properties

Thickener	CaS Complex
Color	Cream
NLGI grade	2
Oil Separation Storage, ASTM D1742, %	<0.5
Dropping point, ASTM D2265, °C(°F)	316(600)
Copper corrosion, 24 hrs. @ 100°C	1b
Density, 25°C, g/cc	1.1
4-Ball Wear, ASTM D2266, average wear scar, mm	0.5
4-Ball EP, Load Wear Index, ASTM D2596, kgf	50
4-Ball EP, Weld point, ASTM D2596, kg	400
Timken® OK Load, ASTM D2509, Kg	25
Water Washout, ASTM D1264, %	<1
Water Sprayoff, ASTM 4049, %	33

### Typical Base Fluid Properties

Base fluid	PAO
ISO Viscosity Grade	100
Viscosity, ASTM D445 @ 40°C, cSt	100
Viscosity Index, ASTM D2270	140

### Material Compatibilities:

Compatible with most engineering plastics including ABS and polycarbonate. Not for use with Buna S, Butyl, EPDM, EPR, or natural rubber elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

07/15 Rev.1

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



---

1550F W. Fullerton Ave.  
Addison, IL 60101 USA  
(630) 628-7290  
[www.syn-techlube.com](http://www.syn-techlube.com)

**Lubricants that Solve Problems**