

NS-2717-G

Water resistant Bearing Lubricant

NS-2717-G is a multipurpose semi-synthetic friction reducing bearing lubricant. Provides enhanced wear protection for non-ferrous metals such as brass and copper. Protects steel against rust and corrosion as well as protecting brass and other non-ferrous metals from corrosion. PTFE fortified for low friction.

Characteristics:

- Resists moisture and humidity
- Reduces friction
- Excellent wear protection for brass
- Protects ferrous and non-ferrous metals from rust and corrosion
- PTFE fortified
- Operating temperature range of -18°C to 125°C

Typical Properties

Thickener	Li Soap
Color	Cream
NLGI grade	2
Penetration, ASTM D1403, worked, 60 Ds	268
Copper corrosion, ASTM D130, 24 hrs. @ 210°F	1b

Typical Base Fluid Properties


Base fluid	Semi-synthetic
------------	----------------

Material Compatibilities:

Compatible with most engineering plastics (including ABS and polycarbonate) and elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

01/18 Rev.0

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA
(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems